CSD 8.5 Release notes

Completed backlog items:

| ID | Title | State | Description |
|------------|---|-------|--|
| 286 | Install date on equipment | Done | 08.11.2016 KFA - tested OK. 03.11.2016 OBE: fixed in 8.5 25.10.2016 KFA - Install date shows in the Properties dialog for each element, but should also show in Item Properties->Item Data.Today we have installation data on inserted equipment but it is a problem that this is not shown on the schematic. Maybe there should be info about this in Symbol extra info? In addition to this the customer would like to note when plugs and patches are installed. Due to this it would be good to have an Installed date on element level for all parts that have been used to build up the string itself. |
| 327 | Log item COMPLETION_OPEN should show the Identifier string. | Done | 08.11.2016 - KFA tested OK.20.10.2016 KFA - Identifier string is showing, but in the Comment column, instead of the Identifier string column.12.10.2016 KFA - Identifier String is blank in Log Type COMPLETION_OPEN. |
| <u>339</u> | Refresh of error column | Done | |
| <u>340</u> | Clean up of document pointers | Done | |
| <u>341</u> | Batch loading of elements | Done | |
| <u>342</u> | Refactoring of wellcompletion pointers | Done | |
| <u>343</u> | Range based for loops in CObList (C++11) | Done | |
| <u>344</u> | Fix compiler warnings for Jpeg2PDF | Done | |
| 345 | Link from error column to failure | Done | Only for elements; not inserted or inner |
| 346 | Hot spots in schematic do not work after moving the mouse inside the header | Done | |
| 347 | Schematic drawing optimization | Done | |
| 348 | Problem when not "MARS" connection (Multiple Active Result Sets) | Done | |
| <u>349</u> | Save optimazation: skip all empty lists | Done | |
| <u>350</u> | Refactoring of multiple wellbores; move data for each wellbore | Done | |

| ID | Title | State | Description |
|------------|---|-------|--|
| | below the CWellCompletion object | | |
| <u>356</u> | Adding / removing wellbore should not be undoable | Done | |
| 360 | Remove Read Only bar after Save. | Done | 2017.07.11 - Kfa: Tested OK. >Ready for test When facing the upper Statusbar: Completion is marked as read only due to automatic datum change, and pressing Save As, then save as a new revisjon, the yellow statusbar is still showing. One has to close and open the revision for the statusbar to disappear. This could be somewhat confusing for users not knowing this. |
| <u>365</u> | Refacture CMapEx into std::map | Done | |
| <u>374</u> | Remove option of making a dual to a single (but not opposite) | Done | 2017.07.12 - Kfa: Tested OK.ref issues at Statoil (Heidrun) and SEEPCO |
| <u>378</u> | Prevent users to toggle to Dual string mode when equipment exists in sec. string mode | Done | If users are unable to toggle from single string to dual string mode when there is equipment registered in secondary string mode, we can prevent this issue from happening. |
| <u>384</u> | Part Failure module | Done | |
| <u>386</u> | Casing-merge in ExternalProvider is inncorrect | Done | |
| 388 | Row color for expired parts not showing | Done | |
| <u>393</u> | CSD crashes when too many characters in the Comments field. | Done | |
| <u>395</u> | Part, Failure: Filter on Revision Drop down. | Done | 2017.07.11 - Kfa: Tested OK.Should be able to turn on and off a filter on the revision drop down in the Part, Failure tab. The filter could follow the Cdim visible flag, as the Excel reports does. |
| <u>396</u> | Control line: when a control goes from on element to another, the save fails | Done | |
| <u>398</u> | Crash when a control line goes to an element, and you delete the to-element | Done | |
| 399 | DocDrive: support for MSAccess | Done | limit to folder structure of one level |
| 400 | CSDDocDrive: R_DOCUMENT_NODE_TYPE is actually NULL for some old documents | Done | |
| <u>401</u> | CSDDocDrive: filter R_APPLICATION=1 and VISIBLE=1 | Done | |
| <u>405</u> | Be able to copy wellbore name column in locked wellbore. | Done | It would sometimes be handy to be able to copy the wellbore name of a locket well. Would it be |

| ID | Title | State | Description |
|------------|--|-------|--|
| | | | possible to allow copying "grey / uneditable" text fields? |
| <u>406</u> | Survey: When pasting and scanning a new set of survey data, the list is not cleared | Done | |
| <u>410</u> | Create sketch points (curve) based on inclination of survey | Done | |
| <u>411</u> | Improve the "copy as image"- functionality with gdi+ | Done | This will make it a lot better when pasing into ie Word |
| 412 | Mapping to DBR: When saving a completion to a new well, the sync data is not cleared | Done | |
| <u>415</u> | CLog::Log::PartEdit should log data before and after editing | Done | |
| <u>416</u> | CLog::Log should also log PartReplace | Done | |
| 417 | Show last Actual only in CSD Explorer | Done | 2017.07.12 - KFA - tested OK. ready for retest. 2017.07.11 - KFAD - Tested on Statoil, no difference in Explorer when enabling. ready for test. Add a button for enable / disable filter on which completion revisions to show in CSD Explorer (but maybe not in the Open dialog?). Show last Existing only could be the default setting in Explorer. |
| 418 | Part, Data: Partnumber column should always be locked for editing | Done | 20170711 - Kfa: Tested OK. Ready for test In reference to the recent Wintershall incident where part info and partnumbers are changed on existing db parts, it would be a great safety precaution to make the partnumber column not editable. It's a small job for the administrator to copy the part and create a new one, if misspelling the partnumber, then delete the part containing the wrong partnumber. |
| <u>419</u> | The system setting "PartEditOwnerAccess" is a boolean value | Done | The system setting "PartEditOwnerAccess" is a boolean value, så it should be true/false in the system settings dialog, and not a number as it is now |
| <u>425</u> | Can not use chinese characters in field and well names | Done | |
| <u>427</u> | In chinese CSD, all XML's produced have wrong header | Done | |
| 430 | Clone main to CSD85 | Done | clone main to CSD85 - open CSD85 - change post build to copy to CSD85 folder - do release build of CSD85 - open main - change version in resource - change version in "csd script update_version.SQL" |

| ID | Title | State | Description |
|------------|--|-------|--|
| <u>431</u> | Can not delete Casing Attribute | Done | Ref well: Troll NO 31/2-M-14 CY1HT2.Can't delete any Casing Attributes in CSD 8.5.0.1. |
| <u>434</u> | DBR: perforation shot density is in x/ft . Convert to x/m | Done | |
| 435 | Load from XML: when a dynamic attribute value (or any variant type in xml) is negative: uncaught exception | Done | |
| <u>454</u> | Clearing of sync data after an unmap does not work | Done | |
| <u>466</u> | SIZE_STR expand to 32 characters | Done | |
| 480 | Version checking not fully functional when checking against only major and minor (ie 7.2) | Done | |